

RXL16 Series

120V/277V

Catalog #:		Type
Project:		Date
Prepared by:		

Die Cast Exit Sign - Double Face



LED Emergency Exit

DESCRIPTION

When normal utility power fails, the internal solid-state transfer switch automatically connects the internal battery to the LED lamps, lighting a path of egress for no less than 90 minutes. When utility power is restored the battery is recharged by the onboard solid-state recharger. Full recharge is accomplished within 24 hours.

DESIGN FEATURES

Construction

- High impact-flame retardant thermoplastic faceplate
- Die cast aluminum housing
- Compact, low profile design
- Completely self-contained
- Universal snap-in and out chevron design meets all state and local codes (UL924)

Electrical

- 120/277V
- Operating temperature: 10°C (50°F) to 40°C (104°F)
- Contains 4.8V Ni-cd rechargeable battery
- Automatic, low voltage disconnect protects battery from deep discharge
- Energy consumption of less than 2 watts for red letters and less than 1 watt for green letters. Estimated 25 year LED lamp life
- Estimated 25 year LED lamp life
- 90 minutes of illumination in case of power failure

Installation

- Ceiling, side or top mountable
- Universal mounting canopy for side or top installation
- Removable directional indicators included
- Easy, one-person installation

Dimensions (W x D x H)

- 12-3/4" x 1-13/16" x 8-7/16"

Finish

- RBA Red with brushed aluminum housing
- GBA Green with brushed aluminum housing

Certifications

- UL listed for damp location
- 5 year limited warranty

ORDERING

Example: RXL16-RW

Model #	Finish	
RXL16		
RXL16	RBA	Red with brushed aluminum housing
	GBA	Green with brushed aluminum housing



TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com

Specifications and dimensions subject to change without notice.