

4313, 4314, 4318-30, 4345-30

120V

Catalog #:		Type
Project:		Date
Prepared by:		


LED Ceiling Mount Fixture



4313, 4314, 4318-30



4345-30



LED Ceiling Mount Fixture

DESCRIPTION

This sleek LED Surface Mount Fixture is an energy efficient LED light that comes complete with an integrated LED light engine - no additional light bulbs needed. This fixture is mounted on a ceiling to provide light anywhere you need it.

DESIGN FEATURES

Construction

- Durable steel construction

Electrical

- 120V
- 10-100% Triac dimmable
- 50,000 hour projected life
- Available in 3000K
- 4313: 15W | 1050lms
- 4314: 20W | 1400lms
- 4318: 28W | 2000lms
- 4345: 35W | 2600lms

Built-in emergency backup

- 43XX-EM

Lens

- Acrylic lens protects LEDs and diffuses glare while allowing for optimum lumen output

Finish

- Available finishes: brushed nickel (BN), oil rubbed bronze (OB), white (WH)

Certifications

- ETL & cETL listed
- Energy Star listed -
- 5 year limited warranty



TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com

Specifications and dimensions subject to change without notice.

4313, 4314, 4318-30, 4345-30

120V

Specification & Ordering

Model No.	Size (W x H)	Finish	Watts	CRI	Lumens	Efficacy (lm/W)	Power Factor	Beam Angle
4313	12" x 3-1/2"	BN OB WH	15	>85	1050	70	0.99	118°
4314	14" x 3-1/2"	BN OB WH	20	>81	1400	70	0.98	116°
4318-30	18" x 4-1/8"	BN OB	28	>81	2000	71.4	0.97	116°
4345-30	32" x 18" x 4"	BN OB	35	>82	2600	74.3	0.99	116°

ORDERING

Example: 4313-BA-3K

Model #	Finish	CCT	Emergency
		-3K	
4313 4314 4318-30 4345-30	BN : Brushed Nickel OB : Oil-rubbed Bronze WH : White	-3K : 3000 K	-EM : Adds battery pack

LED Ceiling Mount Fixture