
Catalog #:	Туре
Project:	Date
Prepared by:	

6" LED Recessed Baffle







DESCRIPTION

This 6" LED Recessed Baffle makes upgrading to an energy efficient LED down light solution easier than ever. This is an ideal choice for most residential or light-commercial application.

DESIGN FEATURES

Construction

- Spun aluminum trim
- Frosted polycarbonate lens

Electrical

- 120V 60Hz
- Contact factory for 277V or 0-10V dimming options
- Dimmable TRIAC or ELV, 10-100%
- 50,000 hour projected life
- 90 = 12W | 728 lms (*delivered*)
- HO-90 = 12.9W | 1208 lms (*delivered*)
- 3000K | 4000K | 90 CRI

Installation

 Included torsion springs and E26 socket adapter for installation in 6" housings

Available Housings

- 8102HAQ
- 8102HRA
- 8102HICA
- 8117HA
- 8117HRA
- 8199HICA-FR

Dimensions

- 7-1/4" x 2-1/2" Overall
- 6-1/4" aperture

Certifications

- · cCSAus Listed for wet location
- Energy Star Listed (8523WH-90 unit only)
- CEC JA8 Compliant (8523WH-90 unit only)
- LED Lamp: 5 Year Limited Warranty
- Other Components: 1 Year Limited Warranty

ORDERING GUIDE Example: 8523WH-HO- 90-3K			
Model #	Finish	CRI	CCT
8523			
8523	WH : White	-90 -HO-90 *	-3K -4K

^{*} HO-90 only available in -3K













TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com



