	Catalog #:	Туре
8822-1	Project:	Date
0022-1 120V	Prepared by:	
3" Recessed Gimbal		
)")"
	3-11/16″	

DESCRIPTION

The 8822-1 - 3" Recessed Gimbal is a quick, easy, and affordable way to upgrade to an energy efficient LED down light solution. For use in new and existing ceilings. An ideal choice for retrofit and remodel in most residential or light-commercial applications.

DESIGN FEATURES

Construction

- Durable steel construction
- Frosted impact-resistant plastic lens

Electrical

- 120V-60Hz
- Dimmable TRIAC, 10-100%
- 50,000 hour projected life
- 10W | 650 lms
- 3000K | 80 CRI

Installation

Simple and easy installation to housing with 3 spring clips

Dimensions

- 3" nominal aperture
- 3-11/16" W x 3" H

Compatible Housing

- 8317H 3" LED IC Rated Frame-In
- 8317HR 3" LED IC Rated Remodel

TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com

Certifications

- cETLus for damp location
- LED Lamp: 5 Year Limited Warranty
- Other Components: 1 Year Limited Warranty

ORDERIN	IG	Example: 8822-1-WH-3K	
Model #	Finish	ССТ	
8822-1		-3K	
8822-1	-WH : White	-3K : 3000K	





LIGHTING · FANS