atalog #:	Туре
roject:	
ojeci.	Date
repared by:	

120V-60Hz

3 CCT Selectable Under Cabinet Light

89xx-2734 Series



DESCRIPTION

This series offers three color temperature options in one product which adds a touch of warmth and elegance to any cabinet/counter top application. Low-profile, easy installation, energy efficient and maintenance free.

DESIGN FEATURES

Construction

- Aluminum housing with Ribbed Acrylic Curved Lens
- Linkable design for hardwire and plug-in

Electrical

- 120V-60Hz
- Dimmable TRIAC, 10-100%
- 50,000 hour projected life •
- CCT Selectable: 2700K, 3000K, 4000K
- 90 CRI •

Installation

- Hinged wiring trough for easy access to wires
- Fast Hard-wiring with snap-in connector
- Each end-cap has one 3/4" knockout and capped linkable socket
- 8966: (1) 1/2" knockout located on the back side of housing
- 8968: (2) 1/2" knockouts located on the back side of housing

Finish

Finish: white (WH)

Available Accessories

- 6" Connector cord: 897CN-6
- 12" Connector cord: 897CN-12
- 24" Power cord: 897PC-24
- End-to-end connector: 897CN
- Lens Replacement: 89xxL

Listing

- cCSAus Listed for damp location
- **Energy Star Listed**
- **CEC JA8 Compliant**
- LED Light Source: 5 Year Limited Warranty
- Other Components: 1 Year Limited Warranty

ORDERING	GUIDE	Example: 8966WH-2734	
Model # Finish		ССТ	
8966 : 9"	WH : White	-2734 : 2700K, 3000K, 4000K	
8968 : 18"			
0900. 10			

See 89xx-5CCT for other Selectable CCT units



1/30/23 R4



ω

TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com

89xx-2734 Series

120V-60Hz

Specification

Model #	Size (L x D x H)	Lumens	Watts	CRI	
8966WH-2734	9" x 3-3/4" x 1-1/16"	Source 320lms, Delivered 250lms	4W	00	
8968WH-2734	18" x 3-3/4" x 1-1/16"	Source 630lms, Delivered 500lms	7W	90	

