
8708-3CCT 120V

Type Catalog #: **Project:** Date Prepared by:

4" LED Round Retrofit Downlight 3CCT Selectable





DESCRIPTION

A slim profile, small aperture downlight that fits in a 4" octagonal j-box with multiple trim-ring finish accessories. Wet location listing, IC rating, and wide distribution makes this an excellent choice for simple illumination in hallway and bathroom applications.

DESIGN FEATURES

Construction


- Durable aluminum construction
- Polycarbonate frosted lens

Electrical

- 120V-60Hz
- Dimmable TRIAC or ELV, 10-100%
- 50,000 hour projected life
- 90 CRI | 11W | 691 lms (delivered)
- 3CCT Selectable
- Beam Angle: 110°
- Operating temperature: 14°F 104°F

Installation

- Simple and easy installation light engine and trim connects via twist and lock
- Installs in 4" Octagonal ceiling j-box (min 2" depth); j-box supplied by others



Die Cast Trim (sold separately)

- 4-JBR-BK: Black
- 4-JBR-BN: Brushed Nickel

Dimensions

4-5/8" x 2-27/32" x 31/32"

Certifications

- cCSAus Listed for wet location
- IC Rated
- LED Lamp: 5 Year Limited Warranty
- Other Components: 1 Year Limited Warranty

ORDER	ING C	UIDE	Example: 8708WH-90-3CCT		
Model #	Finish		CRI	ССТ	
8708	WH		-90	-3CCT	
8708	WH:	White	-90 : 90 CRI	-3CCT : Selectable 27K, 3K,35K	
Accessory		Finish			
4-JBR-BK 4-JBR-BN		Black Trim Ring for 8708 Brushed Nickel Trim Ring for 8708			

For Square Trim, refer to 8709 Specification Sheet









